



## ORiNOCO™ PC Card

Home, Office, and Public Mobile Broadband Internet Access

#### One Card, One Technology, One Solution

The same ORiNOCO PC card can be used for the Enterprise, ISP, Public Access or Home/SOHO markets using any of the ORiNOCO access point infrastructure products. The card provides high-speed wireless networking at 11 Mbit/s, and secure Internet access for laptop and desktop computers, as well as a wide range of mobile client computing devices. The ORiNOCO suite of products builds on Lucent's industry-leading WaveLAN® wireless LAN technology.

#### Freedom to Work Anywhere

ORiNOCO PC Card delivers the same high-performance connectivity as wired systems, with the added freedom to move around your building or campus.

#### Compatible with Industry Standards

The ORiNOCO PC Card is interoperable with other manufacturers' high-speed IEEE 802.11b compliant systems and is fully compliant with the WECA Wi-Fi (wireless fidelity) standard. It is also compatible with Lucent's previous 2 Mbit/s and Turbo products.

### Data Protection and Security

Our ORiNOCO PC Card is designed with a choice of security levels to protect your data. The standard level, 'Silver' PC Card, has wired equivalent privacy (WEP), using a 64-bit key. The 'Gold' version provides enhanced security with a 128-bit key, using RC4 encryption.



# Basic ORiNOCO PC Card configuration

YOUR MOBILE BROADBAND CONNECTION



ORiNOCO PC Card Specifica	2400-2483.5 MH					
Frequency Band Numbers of Selectable	2400-2483.3 MH	Z				
Sub-Channels	11 (USA FCC)					
Modulation Technique		Direct Sequence Spread Spectrum (CCK, DQPSK, DBPSK)				
Spreading	11-chip Barker sequence					
Bit Error Rate	Better than 10 <sup>-5</sup>					
Media Access Protocol		CSMA/CA (Collision Avoidance) with ACK				
Interface	PC card (ISA and PCI adapter cards are available					
Dimensions	117.8 mm X 53.95 mm X 8.7 mm (PC Card)					
Range in meters (feet)		······				
(100 bytes user data)	11 Mbit/s	5.5 Mbit/s	2 Mbit/s		1 Mbit/s	
Open Office	160 m (525 ft)	270 m (885 ft)	400 m (130	00 ft)	550 m (1750 ft)	
Semi Open Office	50 m (165 ft)	70 m (230 ft)	90 m (300	ft)	115 m (375 ft)	
Closed Office	25 m (80 ft)	35 m (115 ft)	40 m (130	ft)	50 m (165 ft)	
Receiver Sensitivity dBm	-82	-87	-91		-94	
Delay Spread (at FER of <1%)	65ns	225ns	400ns		500ns	
Output Power	15 dBm	15 dBm				
Power Consumption PC Card	Doze mode – 9 n	nA Receiver mo	de – 185 mA	Trar	nsmit mode – 285 mA	
5 V power supply) ISA	+25mA					
remperature Range (operational)	0-55° 95% max. humidity (non condensing)					
Compatibility	Novell Client 3.x & 4.x, Windows® 95/98/2000 and					
	Windows NT (NDIS Miniport driver); Apple <sup>®</sup> ; Windows/CE					
Standards	IEEE 802.11b HF	2				
Regulations (USA/FCC/Canada)	USA: Canada:	FCC 47 CFR ISC RSS139	Part 15C, Sect	tion 15	.247	
Warranty	3 years					
Comcodes	- , 5415					
ORINOCO PC Cards						
848 441 481	(FCC); WEP; Silver			For sa	les and additional information contact	
348 441 556	(FCC); 128RC4; Gold			Hyperl Tel: 50	ink Technologies at: sales@hyperlinktech.com 61-995-2256 or Fax: 561-995-2432	
ORINOCO PC Card Accessories				You can also visit Hyperlink's website:		
848 072 559	ISA adapter card	ISA adapter card (without PC Card)			http://www.hyperlinktech.com	
848 463 055	PCI adapter card (without PC Card)			or http://www.orinoco.cc.		
848 072 633	Indoor Range Extender antenna (2.5 dBi)			Apple Comp	is a registered trademark of Apple uter, Inc.	
Orinoco Adapter Cables and Accessor			-	OCO and WaveLAN are trademarks		
CA-WL2CABLE1	<b>vx</b>	ale Adapter Cable 1	or registered trademarks of Lucent			
CA-WL2CABLE4		Orinoco to N-Male Adapter Cable 19"			ologies Inc. in the United States r other countries.	
*****		Prof Ouble 1				
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX				Windows is a trademark or registered trademark of of Microsoft Corp. in the		
*****					d States and/or other countries.	
Hyperlink manufactures a complete li		nas, amplifiers and	accessories		ocument is for planning purposes	
Acronyms		,			and is not intended to modify or ement any specifications or warranties	
EEE — Institute of Electrical and Electronics Engineers				relating to Lucent Technologies products		
ISA — Industry Standard Archite					ervices.	
PCI — Peripheral Component Interconnect				Copyright © 2000 Lucent Technologies Inc. All rights reserved		
SOHO — Small Office Home Office				Printed in U.S.A.		
	thility Allience				Amp and HyperGain are trademarks or	
WECA — Wireless Ethernet Compatibility Alliance				registered trademarks of Hyperlink Technologi in the United States and/or other countries.		
WEP — Wired Equivalent Privacy				in the	child States and of other countries.	
<ul> <li>Key Advantages of the ORINOCO PC Card</li> <li>One single card operates with all ORIN environment.</li> </ul>		ints, for instant acce	ss in every			
<ul> <li>Provides Ethernet-equivalent network from Bell Labs.</li> </ul>						
Consumes very little power, making it     Provides excellent coverage and range						
<ul> <li>Provides excellent coverage and range</li> <li>Offers automatic rate selection: 11 Mb</li> </ul>						

For desktops, Lucent offers an ISA and PCI adapter. Combined with the ORiNOCO PC Card, the adapter allows you to add or relocate networked desktop computers, without having to patch wires or run new cables.

