

Specifications

International Corporate Headquarters

Tel: +972 3 645 6262
 Fax: +972 3 645 6222
 Email: corporate-sales@alvarion.com

North America Headquarters

Tel: +1 760 517 3100
 Fax: +1 760 517 3200
 Email: n.america-sales@alvarion.com

Latin America & Caribbean

Tel: +1 954 746 7420
 Fax: +1 954 746 9332
 Email: lasales@alvarion.com

Brazil

Tel: +55 11 3815 6225
 Fax: +55 11 3813 0467
 Email: brazil-sales@alvarion.com

China

Tel: +86 10 8857 6770
 Fax: +86 10 8857 6772
 Email: china-sales@alvarion.com

Czech Republic

Tel: +420 222 191 233
 Fax: +420 222 191 200
 Email: czech-sales@alvarion.com

France

Tel: +33 1 34 38 54 30
 Fax: +33 1 34 38 54 39
 Email: france-sales@alvarion.com

Germany

Tel: +49 89 90405 923
 Fax: +49 89 90405 922
 Email: germany-sales@alvarion.com

Japan

Tel: +81 3 3556 7327
 Fax: +81 3 3556 5370
 Email: alvarion-japan@alvarion.com

U.K. & Ireland

Tel: +44 845 450 1414
 Fax: +44 845 450 1455
 Email: uk-sales@alvarion.com

Romania

Tel: +40 21 335 7631
 Fax: +40 21 335 7634
 Email: romania-sales@alvarion.com

Russia

Tel: +7 (095) 783 82 31
 Fax: +7 (095) 287 98 99
 Email: info@alvarion.ru

Uruguay

Tel: +598 2 606 2651
 Fax: +598 2 606 2652
 Email: lasales@alvarion.com

Radio

Frequency Range	2.4 - 2.4835 GHz ISM band (ETSI, FCC)		
Radio Type	Direct Sequence Spread Spectrum (DSSS)		
Wireless LAN Standards	Compliant with IEEE 802.11b HR		
Selectable sub Channels	FCC	1-11	
	ETSI	1-13	
	Japan TELEC	1-13	
	France	10-13	
	Output Power (at the antenna port)	FCC	-4, -2, 4, 6, 12, 14, 20, 24
	ETSI	-4, -2, 4, 6, 12, 14	(dBm)
	Japan TELEC	-4, -2, 4, 6, 12, 14	(dBm)
Sensitivity (BER 1E10-6)	Data Rate	Sensitivity	Modulation
	11 Mbps	-85 dBm	256 CCK
	5.5 Mbps	-88 dBm	16 CCK
	2 Mbps	-90 dBm	DQPSK
	1 Mbps	-93 dBm	DBPSK
Processing Gain	10.4 dB Nominal		
Integrated Antenna Type	Flat Panel 16 dBi, 20° Vertical /Horizontal		

Range

Europe/ ETSI (20 dBm EIRP)	Up to 10 km
US FCC	Up to 25 km (15 miles)

Security

Authentication and Data Encryption	64 or 128bit RC4 WEP
Scrambling	Proprietary
Authorization	MAC address based association control

Configuration and Management

Management and Setup	SNMP based enhanced windows platform configuration utility	
Site Survey Tool	Integrated into the configuration utility	
SNMP Agents	MIB II, Bridge MIB, DS.11 Private MIBs	
Software Upgrade	Simultaneous multiple units software upgrade using the configuration utility TFTP download	
LED Indicators	Indoor Interface Unit	Outdoor Unit
	Power status	Power Status
	End-to-end Ethernet status	10-LED display bar:
		RSSI in the RB/ Load Gauge in BU
		Ethernet Status / Traffic
	Wireless Link Status / Traffic	

Outdoor Unit-to-Indoor Unit Communication

Cable Type	Cat 5 FTP 4x2x24 Double Jacket
Maximum Cable length between outdoor unit and end-user equipment	100 m (328 feet)

Interfaces

RF (antenna) connector in the outdoor unit	N-Type jack, lightning protected
Baseband (indoor-to-outdoor units)	Outdoor units: Shielded RJ-45 with special water proof sealed cap
	Indoor units: Shielded RJ-45
Ethernet	Indoor units: 10BaseT, (RJ-45) with 2 embedded LEDs

Electrical

Power Consumption	110VAC, 25W
	220VAC, 24W

Mechanical Dimensions

Outdoor Unit	30.5 x 12 x 5 cm	(12 x 4.7 x 2 in)
Outdoor Unit with Integrated Antenna	30 x 30 x 7.2 cm	(12 x 12 x 2.8 in)
Indoor Unit	16 x 9 x 6cm	(6.3 x 3.5 x 2.3 in)

Environmental

Operating Temperature	Indoor unit: 0°C to 40°C (32°F to 104°F)
	Outdoor unit: -40°C to 55°C (-40°F to 131°F)
Operating Humidity	5% to 95% non-condensing. Outdoor units are weather protected

Standards Compliance, General

EMC	EN 300-385, FCC Part 15
Safety	EN 60950, UL 1950
Environmental	ETS 300 019, Bellcore GR-63-CORE
Wireless LAN Standards	ETSI ETS 300 328, FCC Part 15



www.alvarion.com

© Copyright 2003 Alvarion Ltd. All rights reserved.
 Alvarion, BreezeCOM, WALKair, WALKnet, BreezeNET, BreezeMANAGE, BreezeACCESS, BreezeLINK, BreezePHONE, MGW, eMGW and/or other products and/or services referenced here in are either registered trademarks, trademarks or service marks of Alvarion Ltd. All other names are or may be the trademarks of their respective owners.

BreezeNET DS.11 Wireless Bridging

Secure and robust airwaves

The BreezeNET family of products provides efficient, cost effective, secured point-to-point and point-to-multipoint networking optimized for building-to-building connectivity, covering distances of more than 60 km (37 miles) in harsh and adverse environments and weather conditions.

BreezeNET is the ideal solution for connecting buildings, campuses, industrial zones and remote sites, ensuring enterprise and community-wide network connectivity.

Providing robust outdoor wireless infrastructure for optimal range and capacity, the BreezeNET DS.11 leverages Direct Sequence Spread Spectrum technology, which is ideally suited for fast and consistent building-to-building connectivity, optimizing services to broadband applications in co-located fixed LAN environments.

DS.11 is designed to transmit in the unlicensed 2.4GHz bands. It combines low-cost cabling, easy installation, rapid scalability and seamless integration into existing Ethernet networks to ensure maximum cost efficiency.

Moreover, quick and easy network installation and SNMP remote management, enables rapid deployment of the DS.11 as well as simple expansion in relation to the changing needs of the network environment. BreezeNET ensures uncompromising security to prevent hacking, data theft and hostile intrusions. 128 bit WEP keys, MAC Address based association control and proprietary scrambling are just part of a full security package that is designed to protect the wireless link.



Product Highlights

BreezeNET DS.11 delivers a comprehensive range of product features, ensuring fast, consistent and reliable networking services, including:

- Outdoor architecture ensures unprecedented range and reliability.
- Data rates of up to 11 Mbps.
- Range of more than 60 km (37 miles).
- Multi Layer Security Package including: 128 bit WEP key encryption, MAC Address based association control, proprietary scrambling of data and more.
- Improved performance (Short Preamble and Best BU choice support).
- Full LED diagnostics, featuring 10-LED RSSI bar display for easy antenna alignment.
- Built-in remote diagnostics, which minimize maintenance and maximize savings.
- IEEE 802.11b, IEEE 802.3

BreezeNET DS.11 System Components

BU-DS.11 Base Unit	Connects directly to the 10Base-T Ethernet backbone and links up to 128 remote sites to the central network point.
RB-DS.11 Remote Bridge	Connects directly to the 10Base-T Ethernet LAN and links the remote Ethernet LAN to the central point via the Base Unit, servicing up to 1024 stations.



BreezeNET DS.11

Record-breaking REACH, highly RELIABLE and SECURE

